

**Description:**

- ☆ A Good Fit for Tough Environments
- ☆ High Tensile and Tear Strength
- ☆ Anti-Mildew / Anti-Microbial Treatments & U.V. Pigments
- ☆ Fire Retardant
- ☆ Latex and Rubber Free
- ☆ Matte Finish

**Color Options:**



**Details:**

CATEGORY	TEST RESULT	TEST METHOD
<b>TOTAL WEIGHT</b>	18 oz. per yard <sup>2</sup>	FS 5040 / ASTM D3776
<b>WIDTH</b>	61"	
<b>CONSTRUCTION</b>	19 x 17/1" by 1000 x 1000	
<b>GRAB TENSILE</b>	375 x 375 lbs./1"	FS 5100 / ASTM D5034
<b>TONGUE TEAR</b>	100 x 100 lbs.	FS 5134 / ASTM D2261
<b>ADHESION</b>	26 lbs./2"	FS 5970 / ASTM D751
<b>COLD CRACK</b>	-30° F	FS 5874 / ASTM D 2136
<b>F.R. TREATMENTS</b>	Self-extinguishing / Passes FR	CSFM / NFPA - 701 / ASTM E - 84
<b>TREATMENTS</b>	UV, Anti-microbial, Anti-bacterial, Anti-mildew, Anti-mold	
<b>FINISH</b>	Matte	
<b>PUT UP</b>	75 yards	

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit. These statistics are however, provided only as a convenience and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.