

Description:

- ☆ Extremely Strong and Durable
- ☆ High Tensile and Tear Strength
- ☆ Anti-Mildew / Anti-Microbial Treatments & U.V. Pigments
- ☆ Fire Retardant
- ☆ Leather Grain Finish

Details

CATEGORY	TEST RESULT	TEST METHOD
TOTAL WEIGHT	14 oz./yd ²	ASTM D 751
WIDTH	61"	
CONSTRUCTION	20 x 20/1" by 1000 x 1000	
GRAB TENSILE	580 x 500 lbf / 2 in.	ASTM D 751
TONGUE TEAR	60 x 50 lbf	ASTM D 751
ADHESION	16 lbf / 2 in.	ASTM D 751
COLD CRACK	-30° F	FS 5874 / ASTM D2136
F.R. TREATMENTS	Pass	ASTM E84, CSFM, NFPA - 701
TREATMENTS	UV, Anti-microbial, Anti-bacterial, Anti-mildew, Anti-mold.	
FINISH	Leather Grain	
PUT UP	100 yards	

Color Options:



Black



Grey



**Regal
Blue**



Tan



White

The following information in regards to the chemical and physical properties of this product is based upon reliable testing methods. While reliable, these statistics are intended only as an informational source for your benefit. These statistics are however, provided only as a convenience and do not constitute a warranty and/or guarantee. The Purchaser is still required to determine if the product represented meets the individual needs of the Purchaser.